



HYDRAULIC ELEVATOR POWER UNIT

QUOTATION REQUEST FORM

Date _____

Required Date _____

☐ **Out of Service**

Company _____ Contact _____

Address _____ Phone _____ Ext. _____ Fax _____

City _____ St. _____ Zip _____ Cell Phone _____

Project Name _____ St. _____ Zip _____ Email _____

CAR TYPE

- ☐ Passenger
☐ Freight
Load Class ☐ A ☐ B ☐ C1 ☐ C2 ☐ C3
- ☐ In-ground ☐ Holeless
- ☐ Single Stage ☐ Telescopic ☐ 1:2 Roped
- ☐ Dual Jacks ☐ Cantilever

PROJECT DATA

Capacity _____ lbs

Empty Car Weight _____ lbs

Piston Diameter _____ in

or Circumference _____ in

Piston Wall Thickness _____ in

Total Floor Travel _____ ft _____ in

Car Speed Up _____ fpm

Down _____ fpm
(if different)**or**Static Pressure _____ psi
(empty car at bottom landing)

Flow Rate _____ gpm

Max. Operating Pressure _____ psi

Power Supply _____ V _____ Ph _____ Hz

Coil Voltage _____ V ☐ AC ☐ DC _____ Hz

Existing Horsepower _____ hp

☐ Match Existing Horsepower

Oil Line Size _____ in

☐ Grooved (Std) ☐ NPT☐ Left Hand (Std) ☐ Right Hand

Machine Room Door _____ w _____ h

☐ Machine Room Adjacent☐ Machine Room Remote _____ ft☐ Machine Room Location _____ Landing

POWER UNIT

Quantity Required _____

☐ Submersible ☐ Belt Drive☐ Custom (Specify) _____☐ Use with Biodegradable Oil (Vegetable)☐ Buy American Requirement

Standard Equipment:

- EECO Control Valve
EECO Muffler
Thermal Switch (Preset to 145° F)
Pres. Gauge Fittings & 1/8" Shut Off Valve
Oil Level Sight Gauge
Isolation Anchor Kit
Drip Pan (Belted Only)
Sound Isolation Panels (Belted Only)

OPTIONS

- ☐ Other OEM Control Valve _____ ☐ Adjustable Load Weighing Switch
- ☐ Constant Down Speed ☐ Low Pressure Switch
- ☐ EECO Dampener ☐ N.O. ☐ N.O./N.C.
- ☐ Valve Return Filter ☐ Oil Heater
- ☐ Pre-Wired Power Unit ☐ Viscosity Switch
(Junction Box and Terminals)
- ☐ Low Oil Switch
- ☐ Include Starter ☐ Oil Level Liquid Gauge
- ☐ Y-Delta ☐ ATL ☐ Solid State ☐ Oil Level Dipstick
- ☐ Include Starter Enclosure ☐ Hand Pump for Roped Hydro
- ☐ Tank Mounted ☐ Wall Mounted ☐ Tank Breather
- ☐ Magnetic Tank Drain Plug
- ☐ Tank Shut Off Valve (Belted Only)

ACCESSORIES

- ☐ Oil Cooler ☐ Air ☐ Water ☐ Y-Strainer _____ qty
- ☐ 1000 psi Liquid Filled Pres. Gauge Assy. ☐ Oil Line Fittings (Specify details below)
- ☐ Isolation Coupling _____ qty ☐ Pipe Stand _____ height _____ qty
- ☐ Shut Off Valve _____ qty ☐ EECO Control Valve Adjusting Kit
- ☐ Pipe Rupture Valve _____ qty

☐ Special Requirements