



A Brand of HYPERION

Hydraulic Elevator Power Unit

Quotation Request Form

Required Date _____

Out of Service

Today's Date _____

Company _____

Contact _____

Address _____

Phone _____ Ext _____ Fax _____

City _____ St _____ Zip _____

Mobile _____

Project Name _____ St _____ Zip _____

Email _____

REQUIRED FOR QUOTE

Car Type

- Passenger
- Freight
 - Load Class A B C1 C2 C3
- In-ground Holeless
- Single Stage Telescopic 1:2 Roped
- Dual Jacks Cantilever

Power Unit

Quantity Required _____

Project Data

- Capacity _____ lbs
- Piston Diameter _____ in
- Total Floor Travel _____ ft _____ in
- or No# of stops _____
- Car Speed Up _____ fpm

ADDITIONAL INFO

Project Data

- Empty Car Weight _____ lbs
- Piston Circumference _____ in
- Piston Wall Thickness _____ in
- Car Speed Down _____ fpm
- Static Pressure _____ psi
- Flow Rate _____ gpm
- Full Load Pressure _____ psi
- Power Supply ____V ____Ph ____Hz
- Coil Voltage ____V AC DC ____Hz
- Existing Horsepower ____ hp Match existing hp
- Oil Line Size _____ in
 - Grooved (Std) NPT
 - Left Hand Right Hand
- Machine Room
 - Door _____ W _____ H
 - Adjacent
 - Remote _____ ft
 - Location _____ Landing

POWER UNITS

Power Unit

- Submersible Belt Drive
- Custom (Specify) _____
- _____
- _____
- Buy American Requirement
Quoting US Motors - IMO Pumps

Standard Equipment:

- EECO Control Valve
- EECO Muffler
- 80 Starts per Hour
- Thermal Switch (Preset to 145°F)
- Pres. Gauge Fittings & 1/8" Shut Off Valve
- Oil Level Sight Gauge
- Isolation Anchor Kit
- Drip Pan (Belted Only)
- Sound Isolation Panels (Belted Only)

OPTIONS

- Other OEM Control Valve _____
- Constant Down Speed
- EECO Dampener
- Valve Return Filter
- 120 Starts per Hour
- Pre-Wired Power Unit
(Junction Box and Terminals)
- Low Pressure Switch
 N.O. N.O./N.C.
- Oil Heater
- Viscosity Switch
- Low Oil Switch
- Oil Level Liquid Gauge
- Oil Level Dipstick
- Hand Pump for Roped Hydro
- Tank Breather
- Tank Shut Off Valve (Belted Only)

ACCESSORIES

- Oil Cooler Air Water
- Shut Off Valve _____ qty
- 1000 psi Liquid Filled Pres. Gauge Assy. Pipe Rupture Valve _____ qty
- Isolation Coupling _____ qty Y-Strainer _____ qty

SPECIAL REQUIREMENTS
